SolarEdge Fast Mount 36 For Australia

SFM36



Accelerate backup system installation with the SolarEdge Fast Mount 36

solaradae

- Reduce time, cost, and labour by quickly connecting the SolarEdge Home Hub Inverter and SolarEdge Home Backup Interface
- Simplifies measurements and installation of SolarEdge Home Backup Interface with a dedicated template to mount the Inverter and Backup Interface brackets
- Additional savings from included connection hardware
- Includes an integrated 10-slot ground bar
- Refined design aligns seamlessly with integrated SolarEdge Home products

solaredge

		Units
INSTALLATION SPECIFICATIONS		
Dimensions (W x H x D)	91.4 x 15.24 x 15.24	cm
Weight	3.6	kg
Ambient Temperature Range	-40 to +60	°C
CONSTRUCTION		
Material	Flame retardant, rigid polycarbonate diecast	
STANDARD COMPLIANCE		
Safety	UL 1741, IP14	

© SolarEdge Technologies, Ltd. All rights reserved. SOLAREDGE, the SolarEdge logo, OPTIMIZED BY SOLAREDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc. All other trademarks mentioned herein are trademarks of their respective owners. Date: November 27, 2024 DS-000230-AUS. Subject to change without notice.