

# Residential Power Optimiser For Australia

S440 / S500 / S500B / S650B



POWER OPTIMISER

## PV power optimisation at the module level

- Specifically designed to work with SolarEdge inverters
- Detects abnormal PV connector behavior, preventing potential safety issues\*
- Module-level voltage shutdown for installer and firefighter safety
- Superior efficiency (99.5%)
- Mitigates all types of modules mismatch- loss, from manufacturing tolerance to partial shading
- Flexible system design and compatible with bifacial PV modules for maximum space utilisation
- Faster installations with simplified cable management and easy assembly using a single bolt
- Next generation maintenance with module safety

\* Functionality subject to inverter model and firmware version

# / Residential Power Optimiser

## For Australia

S440 / S500 / S500B / S650B

	S440	S500	S500B	S650B	Units
<b>INPUT</b>					
Rated Input DC Power <sup>(1)</sup>	440	500		650	W
Absolute Maximum Input Voltage (Voc)	60		125	85	Vdc
MPPT Operating Range	8 – 60		12.5 – 105	12.5 – 85	Vdc
Maximum Short Circuit Current (Isc) of Connected PV Panel	14.5	15			Adc
Maximum Efficiency	99.5				%
Weighted Efficiency	98.8				%
Overvoltage Category	II				
Input Overcurrent Protection	15				Adc
<b>OUTPUT DURING OPERATION</b>					
Maximum Output Current	15				Adc
Maximum Output Voltage	60		80		Vdc
<b>OUTPUT DURING STANDBY (POWER OPTIMISER DISCONNECTED FROM INVERTER OR INVERTER OFF)</b>					
Safety Output Voltage per Power Optimiser	1 ± 0.1				Vdc
<b>STANDARD COMPLIANCE</b>					
EMC	FCC Part 15 Class B, IEC61000-6-2, IEC61000-6-3				
Safety	IEC62109-1 (class II safety), UL1741				
Material	UL94 V-0, UV Resistant				
RoHS	Yes				
Fire Safety	VDE-AR-E 2100-712:2018-12				
<b>INSTALLATION SPECIFICATIONS</b>					
Maximum Allowed System Voltage	1000				Vdc
Dimensions (W x L x H)	129 x 155 x 30		129 x 165 x 45		mm
Weight	720		790		gr
Input Connector	MC4 <sup>(2)</sup>				
Input Wire Length	0.1 / 0.9 <sup>(3)</sup>	0.1			m
Output Connector	MC4				
Output Wire Length	(+ ) 2.3, (- ) 0.10				m
Operating Temperature Range <sup>(4)</sup>	-40 to +85				°C
Protection Rating	IP68 / NEMA6P				
Relative Humidity	0 – 100				%

(1) Rated power of the module at STC will not exceed the Power Optimiser Rated Input DC Power. Modules with up to +5% power tolerance are allowed.

(2) For other connector types please contact SolarEdge. Please note that with other connector types, the wire length will be 0.16m. The Sense Connect feature will not detect thermal events on these connectors.

(3) The Sense Connect feature will not detect thermal events on input connectors when the input wire length is 0.9m.

(4) Power de-rating is applied for ambient temperatures above +85°C for S440 and S500, and for ambient temperatures above +75°C for S500B. Refer to the [Power Optimisers Temperature Derating Technical Note](#) for more details.

PV System Design Using a SolarEdge Inverter <sup>(5)</sup>	SolarEdge Home Genesis / SolarEdge Home Hub	Three Phase Residential	Three Phase Commercial	Units
Minimum String Length (Power Optimisers)	S440, S500 S500B, S650B	8 6	9 8	16 14
Maximum String Length	25	25	50	
Maximum Nominal Power per String	5700	5625	11,250	W
Maximum Allowed Connected Power per String <sup>(6)</sup> (In multiple string designs, the maximum is permitted only when the difference in connected power between strings is 2,000W or less)	6800 <sup>(7)</sup>	6800 <sup>(7)</sup>	13,500 <sup>(8)</sup>	
Parallel Strings of Different Lengths or Orientations	Yes			

(5) It is not allowed to mix S-series and P-series Power Optimisers in new installations in the same string.

(6) If the inverter's rated AC power ≤ maximum nominal power per string, then the maximum connected power per string will be able to reach up to the inverter's maximum input DC power. Refer to the [Single String Design Guidelines](#) application note for more details.

(7) For inverters with a rated AC power ≥ 7000W that are connected to at least two strings.

(8) In multiple string designs, it is allowed to install up to 13,500W per string when the difference in the connected power between strings is 2000W or less.

