

# Three Phase Inverter with Synergy Technology For the 208V Grid for North America

SE50KUS



## Powered by unique pre-commissioning process for rapid system installation

- Pre-commissioning feature for automated validation of system components and wiring during the site installation process and prior to grid connection
- Easy 2-person installation with lightweight, modular design (each inverter consists of 3 Synergy units and 1 Synergy Manager)
- Independent operation of each Synergy unit enables higher uptime and easy serviceability
- Built-in thermal sensors detect faulty wiring ensuring enhanced protection and safety
- Built-in arc fault protection and rapid shutdown
- Built-in PID mitigation for maximized system performance
- Monitored\* and field-replaceable surge protection devices, to better withstand surges caused by lightning or other events
- Built-in module-level monitoring with Ethernet or cellular communication for full system visibility

\*Applicable only for DC and AC SPDs

# / Three Phase Inverter with Synergy Technology

## For the 208V Grid for North America

### SE50KUS

MODEL NUMBER	SExxK-USx2lxxxx	UNITS
APPLICABLE TO INVERTERS WITH PART NUMBER	SE50KUS	
<b>OUTPUT</b>		
Rated AC Active Output Power	50000	W
Maximum AC Apparent Output Power	50000	VA
AC Output Line Connections	3W + PE, 4W + PE	
Supported Grids	WYE: TN-C, TN-S, TN-C-S, TT, IT, Delta: IT	
AC Output Voltage Minimum-Nominal-Maximum <sup>(1)</sup> (L-N)	105 – 120 – 132.5	Vac
AC Output Voltage Minimum-Nominal-Maximum <sup>(1)</sup> (L-L)	183 – 208 – 229	Vac
AC Frequency Min-Nom-Max <sup>(1)</sup>	59.5 – 60 – 60.5	Hz
Maximum Continuous Output Current (per Phase, PF=1)	139.5	Aac
GFDI Threshold	1	A
Utility Monitoring, Islanding Protection, Configurable Power Factor, Country Configurable Thresholds	Yes	
Total Harmonic Distortion	≤ 3	%
Power Factor Range	±0.85 to 1	
<b>INPUT</b>		
Maximum DC Power (Module STC) Inverter / Synergy Unit	87500 / 29165	W
Transformer-less, Ungrounded	Yes	
Maximum Input Voltage DC+ to DC-	600	Vdc
Operating Voltage Range	370 – 600	Vdc
Maximum Input Current	3 x 46.5	Adc
Reverse-Polarity Protection	Yes	
Ground-Fault Isolation Detection	167kΩ sensitivity per Synergy Unit <sup>(2)</sup>	
CEC Weighted Efficiency	97	%
Nighttime Power Consumption	< 12	W
<b>ADDITIONAL FEATURES</b>		
Supported Communication Interfaces <sup>(3)</sup>	2 x RS485, Ethernet, Wi-Fi (optional), Cellular (optional)	
Smart Energy Management	Export Limitation	
Inverter Commissioning	With the SetApp mobile application using built-in Wi-Fi access point for local connection	
Arc Fault Protection	Built-in, User Configurable (According to UL1699B)	
Photovoltaic Rapid Shutdown System	NEC 2014, 2017 and 2020, Built-in	
PID Rectifier	Nighttime, built-in	
RS485 Surge Protection (ports 1+2)	Type II, field replaceable, integrated	
AC, DC Surge Protection	Type II, field replaceable, integrated	
DC Fuses (Single Pole)	25A, integrated	
Pre-Commissioning	Built-in <sup>(4)</sup>	
<b>DC SAFETY SWITCH</b>		
DC Disconnect	Built-in	
<b>STANDARD COMPLIANCE</b>		
Safety	UL1699B, UL1741, UL1741 SA, UL1741 SB, UL1998, CSA C22.2#107.1, Canadian AFCI according to T.I.L. M-07	
Grid Connection Standards	IEEE 1547-2018, Rule 21, Rule 14 (HI)	
Emissions	FCC part 15 class A	

(1) For other regional settings please contact SolarEdge support.

(2) Where permitted by local regulations.

(3) For specifications of the optional communication options, visit the [Communication product page](#) or the [Knowledge Center](#) to download the relevant product datasheet.

(4) Not available for P/Ns SExxK-xxxxBPxx.

# / Three Phase Inverter with Synergy Technology

## For the 208V Grid for North America

### SE50KUS

MODEL NUMBER		SExxK-USx2lxxxx	
APPLICABLE TO INVERTERS WITH PART NUMBER		SE50KUS	UNITS
<b>INSTALLATION SPECIFICATIONS</b>			
Number of Synergy Units per Inverter		3	
AC Max Conduit Size		2 ½"	in
Max AWG Line / PE		4/0 / 1/0	
DC Max Conduit Size		1 x 3"; 2 x 2"	in
DC Input Inverter / Synergy Unit	Multi-input (SExxK-USxxxxZ4)	12 / 4 pairs; 6 – 12 AWG	
	Combined input (SExxK-USxxxxW4)	3 pairs / 1 pair, Max 2 AWG; copper or aluminum	
Dimensions (H x W x D)		Synergy Unit: 22 x 12.9 x 10.75 / 558 x 328 x 273 Synergy Manager: 14.17 x 22.4 x 11.6 / 360 x 560 x 295	in / mm
Weight		Synergy Unit: 70.4 / 32 Synergy Manager: 39.6 / 18	lb / kg
Operating Temperature Range		-40 to +140 / -40 to +60 <sup>(5)</sup>	°F / °C
Cooling		Fan (user replaceable)	
Noise		< 67	dBA
Protection Rating		NEMA 3R	
Mounting		Brackets provided	

(5) For power de-rating information refer to the [Temperature Derating Technical Note for North America](#).

SolarEdge is a global leader in smart energy technology. By leveraging world-class engineering capabilities and with a relentless focus on innovation, SolarEdge creates smart energy solutions that power our lives and drive future progress.

SolarEdge developed an intelligent inverter solution that changed the way power is harvested and managed in photovoltaic (PV) systems. The SolarEdge DC optimized inverter maximizes power generation while lowering the cost of energy produced by the PV system.

Continuing to advance smart energy, SolarEdge addresses a broad range of energy market segments through its PV, storage, EV charging, UPS, and grid services solutions.

-  SolarEdge
-  @SolarEdgePV
-  @SolarEdgePV
-  SolarEdgePV
-  SolarEdge
-  [www.solaredge.com/corporate/contact](http://www.solaredge.com/corporate/contact)

**[solaredge.com](http://solaredge.com)**

© SolarEdge Technologies, Ltd. All rights reserved. SOLAREEDGE, the SolarEdge logo, OPTIMIZED BY SOLAREEDGE are trademarks or registered trademarks of SolarEdge Technologies, Inc. All other trademarks mentioned herein are trademarks of their respective owners. Date: March 2, 2024 DS-000037-NAM Subject to change without notice.

Cautionary Note Regarding Market Data and Industry Forecasts: This brochure may contain market data and industry forecasts from certain third-party sources. This information is based on industry surveys and the preparer's expertise in the industry and there can be no assurance that any such market data is accurate or that any such industry forecasts will be achieved. Although we have not independently verified the accuracy of such market data and industry forecasts, we believe that the market data is reliable and that the industry forecasts are reasonable.

